

# HARVESTBELTS Datasheet

**HARVESTGRIP**  
truly endless belts

**HARVESTVEE**  
truly endless & open roll v-belts



## TENSILE CORE

### CTK 1000 ARAMIDIC CORD

BREAKING STRENGTH N/mm	ELONG. AT BREAK %	WORKING LOAD daN/cm	ELONG. AT WORKING LOAD %
≥ 1000	≥ 5	120<x<240	1<x<2

for truly endless belts and v-belts

### EP 125 FABRIC

BREAKING STRENGTH N/mm	ELONG. AT BREAK %	NUMBER OF PLYS	MATERIAL
≥ 900	≥ 22	7	Polyester

for high tight joining clip

## PROFILE RANGE




B SECTION  
(17X11)



C SECTION  
(22X14)



D SECTION  
(32X20)



CUSTOM  
PROFILE


## TOP PROFILE




R1



R2




R6



RA



RR



R15

RUBBER COVER TYPE	HARDNESS Sh.A	BREAKING STRENGTH N/mm <sup>2</sup>	ELONG. AT BREAK %	ABRASION mm <sup>3</sup> (DIN 53516)	COLOR
NR 65 BL	65 ± 5	≥ 16	≥ 450	110 ± 10	BLACK
NR 70 WT	70 ± 5	≥ 20	≥ 500	90 ± 10	WHITE

## BOTTOM SIDE

FABRIC	FIBER (Warp)	FIBER (Weft)	STRUCTURE	FIBER ORIENTATION
TCP	Polyester	Cotton	Textile	45°



RR Endless